



SYR Green Scrubbing Floor Pad

TECHNICAL DATA SHEET

1.0 Description

The Green Scrubbing Floor Pad is constructed of polyester fibres in a semi open texture non-woven fabrication and contains antimicrobial treatment. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable binder/adhesive.

2.0 Intended Use

The Green Floor Pad is designed for deep scrubbing or light stripping. This floor pad will aggressively remove dirt and scuff marks from heavily soiled floors and is ideal for removing worn or damaged floor finishes, providing a fresh new surface ready for recoating. Use with a water based cleaning solution to scrub hard floor surfaces.

Floor pads are intended for use on standard speed rotary floor cleaning machines or automatic scrubber-dryers.

Suitable for use on machine speeds of 175-350 rpm.

3.0 Construction

Made of 100% recycled PET fibres and 100% water based latex resins. Floor pads are designed to be used on both sides.

4.0 Packaging and Marking

Labelling is to clearly identify product and quantity.

5.0 Directions for Use of Floor Pads

Dust mop or sweep floors prior to scrubbing. Use pad until soil and finish have been removed from the floor. Pick up cleaning solution with a mop, wet vacuum or automatic scrubber-dryer. Rinse floor and leave to dry prior to recoating or opening to traffic.

6.0 Product Care of Floor Pads

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. Do not clean the pad in a washing machine. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

7.0 Properties

| Property | Value | Test Method |
|--------------------|--|----------------|
| Thickness | 1.0 – 1.2 in | D5736-95 |
| Weight | 1323 - 1789 g/m ² 38.9 – 52.6 oz/yd ² | D6242-98 |
| Fibre Type | PET 100% Recycled | --- |
| Binder System | Synthetic Blend | --- |
| Binder Application | Spray/Spray | --- |
| Abrasive | Aluminium Oxide | Schieffer Test |
| Colour | Green | --- |

8.0 Floor Pad Sizes available

From 6" - 21" diameter

9.0 Environmental commitment

PET fibre used in our pads comes from 100% post-consumer and industrial recycled waste product.

SYR certification: ISO 9001 Quality Management Systems

Material manufactured under environmental regulations.

Note: Due to the properties of the material and variable conditions of use, there may be variations in the specifications. Please contact SYR with any questions about the product.

SCOT YOUNG RESEARCH LTD., Lye By-Pass, Lye, Stourbridge, West Midlands DY9 8HG United Kingdom.

T: +44 (0)1384 421421 E: sales@syr-clean.com W: www.syr-clean.com