



SYR **Brown** Stripping Floor Pad

TECHNICAL DATA SHEET

1.0 Description

The Brown Stripping Floor Pad used for medium duty stripping is constructed of polyester fibres in an open texture non-woven fabrication and also contains an antimicrobial treatment. Abrasive particles are distributed throughout the material and adhered to the non-woven construction with a sturdy binder/adhesive.

2.0 Intended Use

The Brown Floor Pad should preferably be used with a water based floor stripping solution, to remove worn and soiled floor finishes or sealers. It can also be used to clean heavily soiled hard floor surfaces, such as concrete, when used with a suitable cleaning solution. The Brown Floor Pad is very strong and can be used for dry stripping applications too, such as removal of floor waxes, dirt and old finishes, leaving the surface suitable for immediate recoating. The Floor Pad can even adapt to clean uneven floors.

Floor pads are intended for use on standard speed rotary floor cleaning machines or automatic scrubber-dryers.

Suitable for use on machine speeds of 175-350 rpm.

3.0 Construction

Made of 100% recycled PET fibres bonded with 100% water based latex resins. Floor pads are designed to be used on both sides.

4.0 Packaging and Marking

Labelling is to clearly identify product and quantity.

5.0 Directions for Use of Floor Pads

Dust mop or sweep floors prior to stripping. Use pad until soil and finish have been removed from the floor. Pick up stripping or cleaning solution with a mop/squeegee, wet vacuum or automatic scrubber-dryer. Rinse floor and leave to dry prior to recoating or opening to traffic.

6.0 Product Care of Floor Pads

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. Do not clean the pad in a washing machine. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

7.0 Properties

Property	Value	Test Method
Thickness	1.0 – 1.2 in	D5736-95
Weight	1517 – 2051 g/m ² 44.6 – 60.3 oz/yd ²	D6242-98
Fibre Type	PET 100% Recycled	---
Binder System	Synthetic Blend	---
Binder Application	Spray/Spray	---
Abrasive	Aluminium Oxide	Schieffer Test
Colour	Brown	---

8.0 Floor Pad Sizes available

From 6" - 21" diameter

9.0 Environmental commitment

PET fibre used in our floor pads comes from 100% post-consumer and industrial recycled waste material.

SYR certification: ISO 9001 Quality Management Systems

Material manufactured under environmental regulations.

Note: Due to the properties of the material and variable conditions of use, there may be variations in the specifications. Please contact SYR with any questions about the product.

SCOT YOUNG RESEARCH LTD., Lye By-Pass, Lye, Stourbridge, West Midlands DY9 8HG United Kingdom.

T: +44 (0)1384 421421 E: sales@syr-clean.com W: www.syr-clean.com