



# SYR Black Stripping Floor Pad

## TECHNICAL DATA SHEET

### 1.0 Description

The Black Stripping Floor Pad used for heavy duty wet stripping is constructed of polyester fibres in an open texture non-woven fabrication and also contains an antimicrobial treatment. Abrasive particles are distributed throughout the material and adhered to the non-woven construction with a sturdy binder/adhesive.

### 2.0 Intended Use

The Black Floor Pad is of a highly aggressive material and should preferably be used with a water based floor stripping solution, to strip off and remove worn, soiled, floor finishes or sealers. It can also be used for heavy duty deep cleaning of concrete and industrial floors and all heavily soiled hard floor surfaces, when used in conjunction with suitable cleaning solutions. It prepares floors for recoating, quickly and easily cutting through old finish, dirt and build-up. The Black Floor Pad can even adapt to clean uneven floor surfaces.

Floor pads are intended for use on standard speed rotary floor cleaning machines or automatic scrubber-dryers.

Suitable for use on machine speeds of 175-350 rpm.

### 3.0 Construction

Made of 100% recycled PET fibres and 100% water based latex resins. Floor pads are designed to be used on both sides.

### 4.0 Packaging and Marking

Labelling is to clearly identify product and quantity.

### 5.0 Directions for Use of Floor Pads

Dust mop or sweep floors prior to stripping. Use pad until soil and finish have been removed from the floor. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber-dryer. Rinse floor and leave to dry prior to recoating or opening to traffic.

### 6.0 Product Care of Floor Pads

To prolong the life of this product it may be washed using a hose with a pressure spray nozzle to remove soil. Do not clean the pad in a washing machine. To dissolve heavy soil or finish this pad may be soaked in detergent or diluted stripping solution prior to washing.

### 7.0 Properties

Property	Value	Test Method
Thickness	0.9 – 1.1 in	D5736-95
Weight	1591.8 – 2149.6 g/m <sup>2</sup> 46.8 – 63.2 oz/yd <sup>2</sup>	D6242-98
Fibre Type	PET 100% Recycled	---
Binder System	Synthetic Blend	---
Binder Application	Spray/Dip	---
Abrasive	Aluminium Oxide	Schieffer Test
Colour	Black	---

### 8.0 Floor Pad Sizes available

From 6" - 21" diameter

### 9.0 Environmental commitment

PET fibre used in our floor pads comes from 100% post-consumer and industrial recycled waste material.

SYR certification: ISO 9001 Quality Management Systems Material manufactured under environmental regulations.

Note: Due to the properties of the material and variable conditions of use, there may be variations in the specifications. Please contact SYR with any questions about the product.

SCOT YOUNG RESEARCH LTD., Lye By-Pass, Lye, Stourbridge, West Midlands DY9 8HG United Kingdom.

T: +44 (0)1384 421421 E: [sales@syr-clean.com](mailto:sales@syr-clean.com) W: [www.syr-clean.com](http://www.syr-clean.com)